



ZCOMAX Technologies, Inc.
 14545 Valley View Ave, Suite S
 Santa Fe Springs, CA 90670

Tel: (562) 926-4588
 Fax: (562) 926-7885

ZCOMAX Technologies, Inc.
 98 Ford Road, Suite 3F
 Denville, NJ 07834

Tel: (973) 664-0310
 Fax: (973) 664-0313

XG-602MB IEEE 802.11 b/g WLAN MiniPCI Card

HOST INTERFACE		
33MHz 32-bit MiniPCI, Type III A		
RADIO		
Chipset	Globespan Virata Javelin Chipsets	
Antenna	Two UFL Connectors	
Frequency	USA (FCC) 11 Channels: 2.412GHz-2.462GHz	
	Europe (ETSI) 13 Channels: 2.412GHz-2.472GHz	
	Japan (TELEC) 14 Channels: 2.412GHz-2.483GHz	
Modulation	11g Orthogonal Frequency Division Multiplexing (64QAM, 16QAM, QPSK, BPSK)	
	11b Direct Sequence Spread Spectrum (CCK, DQPSK, DBPSK)	
Output Power	11g	64QAM 14
		16QAM 15
		QPSK 16
		BPSK 17
	11b	DBPSK, DQPSK, CCK 17
Data Rate	11g mode: 54, 48, 36, 24, 18, 12, 9, 6 Mbps	
	11b mode: 11, 5.5, 2, 1 Mbps	
Power Consumption	11g: TX: 480mA; RX: 340mA (max)	
	11b: TX: 430mA; RX: 340mA (max)	
Voltage	3.3V ± 5%	
PHYSICAL SPECIFICATIONS		
Dimension	59.6mm(L)*50.8mm(W)*3.25mm(H)	
Weight	<15g	
ENVIRONMENTAL SPECIFICATIONS		
	Temperature (Ambient)	Humidity (non-condensing)
Operating	0~55 °C	5~80%
Storage	-10~65 °C	5~80%
SUPPORTED OPERATING SYSTEMS		
Win98SE/ME/2000/XP		
SECURITY		
WEP	64/128-bit WEP Encryption	